

SECURITHERM dual control shower panel

Ref. 792334

Time flow thermostatic and mechanical dual control

2025 UK public price excluding VAT:



DESCRIPTION

SECURITHERM dual control shower panel - Ref. 792334

Dual control thermostatic shower panel:
 Large model satin stainless steel shower panel for wall mounted, exposed installation.
 With concealed inlet via flexibles, M $\frac{1}{2}$ ".
 SECURITHERM thermostatic shower mixer.
 Adjustable temperature control from cold water up to 38°C with 1st limiter set at 38°C and 2nd limiter set at 41°C.
 Anti-scalding failsafe: automatic shut-off if cold water fails.
 Anti-cold showers function: automatic shut-off if hot water fails.
 Chrome-plated, tamperproof, scale-resistant, fixed, ROUND shower head with automatic flow rate regulation at 6 lpm at 3 bar.
 Handset with removable flexible via push-fit rapid STOP connector, wall support supplied.
 Time flow valve ~30 seconds with soft-touch operation to control the ROUND shower head
 Non-time flow valve to control the handset with flexible hose.
 Stopcocks.
 Concealed fixings.
 Filters and non-return valves.
 Shower panel suitable for people with reduced mobility.
 30-year warranty.





TECHNICAL CHARACTERISTICS

SECURITHERM dual control shower panel - Ref. 792334

Connector	M $\frac{1}{2}$ "
Technology	Non-time flow and time flow
Height	1,220mm
Depth	100mm
Width	250mm
Flow rate	6 lpm
Temperature limiter	Thermostatic
Finish	Stainless steel
Norms	ACS  
Warranty	



ADVANTAGES

-  Thermostatic temperature regulation
-  Immediate shut-off if cold water fails
-  Fixed or handheld shower head
-  Stainless steel body, brass controls

